

Erb & Roberts, Inc.



AF SERIES DISC PLOW



The model AF Disk Plow is designed for extra strength and offers a wide range of adjustments that permit efficient operation under all types of field and soil conditions.

Optional:

- Adjustable Depth control wheel (CR).

Standard Features:

- Heavy duty frame.
- Category I or II brackets for universal three point lift.
- Adjustments to control width of cut and depth of penetration.
- Disc blades and furrow wheel mounted on tapered roller bearings.
- Adjustable furrow wheel and cross-shaft.
- Equipped with parking stand and tool kit.

Model	AF 2	AF 3	AF 4	AF 5
Number of Disk Blades	02	03	04	05
Disk Blade Dimensions	26" x 4,75 mm or 28" x 6,0 mm			
Spacing	22" (570 mm)	22" (570 mm)	22" (570 mm)	22" (570 mm)
Working Width	550 - 650 mm	800 - 920 mm	1020 - 1230 mm	1280 - 1550 mm
Depth of Cut	150 a 250 mm			
Weight (26" Disk Blades)	690 lb. (314 kg)	896 lb. (408 kg)	1,082 lb. (492 kg)	1,307 lb. (594 kg)
Tractor hp Required	45 - 50	60 - 70	80 - 95	105-120

*Drawbar pounds pull (drawbar horsepower) required varies according to soil conditions and weight added to harrow. Materials and specifications subject to change without notice.